MPN: ELECTRA-P2-30W-1

PoE Injector 30W 802.3af/at



OVERVIEW

Ernitec PoE injectors provides different power and highspeed Ethernet data connection anywhere in your network infrastructure. Some of them come with industrial chipsets
that can work at -40°C ~ 80°C harsh environments. Ernitec PoE injectors are protected by a high-quality metal shell to ensure a long service life. They have passed a series
of strict tests and provides you with reliable performance.

FEATURES:

Compatible with 802.3af/at
Ernitec PoE injectors are compatible with both 802.3af/at/bt, and allow users to lexibly deploy standard and highpowered devices to transfer data and power simultaneously through one Ethernet cable for up to 100 meters. Save your Cable and Time
Your IP camera and wireless AP will not be limited by the locations without a power outlet and no additional AC wiring. Most ost of all, it reduces installation time.
Supports Desktop or Wall Mount These PoE injectors are suitable for use on a desktop or in a wall-mount installation and meet your different environments.

Easy to Install:

Zero configuration, simply connect the injectors to an Ethernet Switch and to the IP-based PoE device to provide power and data for the network with a compact and lightweight design.

Tekniset tiedot

Features	**LED indicators**	Power
	Number of fans	0 ventilátor/ventilátory
Network	**Cabling technology**	10/100BASE-T
	Duplex system	Full
	Forwarding rate	1100 Mpps
	Networking standards	IEEE 802.3af, IEEE 802.3at
	Power over Ethernet (PoE)	Yes
	Supported network protocols	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m)
Operational conditions	**Operating temperature (T-T)**	-10-50 °C
Package dimensions	**Depth (package,cm)**	8 cm
	Gross Weight (Package, kg)	0,55 kg
	Height (package,cm)	19 cm
	Width (package,cm)	10 cm
Packaging content	**Number of products included**	1 kusů

Packaging content	**Power cord included**	Yes
	Quick installation guide	Yes
Ports & interfaces	**RJ-45 input ports**	1
	RJ-45 output ports	1
Power	**Power over Ethernet (PoE) power per port**	30 Watt
Product dimensions	**Height (product,cm)**	14 cm
	Net Weight (Product, kg)	0,3 kg
	Product Depth	3,25 cm
	Product Width	6,2 cm
Vendor information	**Brand Name**	Ernitec
	Warranty	5 Vuosi(a)

Muut kuvat